

ENGINEERED TO SERVE

# Pioneer II XL

Pioneer II XL is an evolution of our feature-packed Type II ambulance, built on a durable ProMaster® 2500 159" chassis with 8,900 lbs GVWR. Inspired by our Pioneer II, Pioneer II XL expands into Bariatric care and meets or exceeds KKK-A-1822F requirements.



## Standard Features

- 3,000-watt full sine wave inverter
- Six 110V dual outlets with 4 USB ports
- Two 12V outlets
- Deep-cycle backup battery
- Advanced electrical system
- Auto-eject shore power
- All aluminum, LED-lit cabinets with Lucite doors
- Tri-mode LED cabin lighting
- Locking meds safe
- Digital main O<sub>2</sub> system with auto shutoff
- Easy-load main oxygen tank
- No-idle HVAC system
- 35,000-lumen emergency lights
- Rear flip-up step
- 6-point restraints

## Options

- Electrical option pre-wires
- EKG monitor slide-out drawer
- Command seat upgrades
- UV sanitizer
- Independent rooftop A/C
- Shoreline heating & cooling
- Additional deep-cycle battery
- RFID locking med box
- IV solution heating/cooling unit
- Retention systems
- Yellow grab handles

### > EXTERIOR





## > INTERIOR



## Why Pioneer II XL?

- ✓ Designed for bariatric care with a 44" expanded cabinet to bench spacing
- ✓ Industry-leading 6' 4" interior height with low 8' 6" exterior clearance
- ✓ 21" load height and 36' turning radius
- ✓ EMT-engineered working environment
- ✓ Ambulance system reduces squad workload
- ✓ Best-in-class value
- ✓ Safest Type II available
- ✓ Dynamically crash-tested - Safety tech package included
- ✓ Most efficient ambulance on the market
- ✓ Most comfortable patient area in a Type II
- ✓ 5 year / 100,000-mile powertrain warranty



[frconversions.com](http://frconversions.com)



Innovative, best-in-class ambulances — built by EMS professionals, for EMS professionals.

Engineered to Serve.

### CONTACT US

1231 Tech Court Westminster, MD 21157  
(844) 372-8267 | [sales@frconversions.com](mailto:sales@frconversions.com)